

Coax10 AD 10 S

CATV Drop Cable



Application

Drop cables are used in private and commercial TV signal distribution networks and as antenna cable for terrestrial and satellite broadcast systems. This predestined **headend cable** is manufactured with vacuum technology. The cable layers thereby have high friction forces which allow automatic dismantling also at small lengths.

Standards

Screening Class A acc. to EN 50117-2-1, EN 50117-2-2, EN 50117-2-4 and EN 50117-2-5, further EN 50083-2/A1, EN 50117-1

Flame resistance

FRNC-C: IEC 60332-3

Construction

Inner conductor	bare copper wire, diameter 1.0 mm
Insulation	gas injected foam PE, diameter 4.55 mm
Outer conductor	Al-PET foil, longitudinal, bonded to the insulation, under tinned copper braid, optical coverage 70%, + Al-PET foil longitudinal, bonded to the sheath, diameter 5.5 mm
Sheath	FRNC, diameter 6.8 mm ± 0.2 mm Black (RAL 9010), white, blue
Printing	DRAKA COAX10 AD 10 S FRNC-C - Class A DIN EN 50117-2-4 + batch number + meter marking

Mechanical properties

Minimum bending radius	without load	5 x D (D= outer diameter)
	with load	10 x D (D= outer diameter)
Temperature range	during operation	- 40° C to + 70° C
	during storage	- 40° C to + 70° C
	during installation	- 5° C to + 60° C
Corrosivity	FRNC-C	acc. to IEC 60754-2
Friction forces between cable layers:		
dielectric – foil – braid – foil – sheath	pull test with 300mm overlapping zone	> 80 N
inner conductor – dielectric acc. to DIN EN 50289-3-17	push test with 50mm overlapping zone	> 15 N

Coax10 AD 10 S

Electrical properties

at 20°C

DC resistance	Inner conductor	22 Ω/km
	Outer conductor	14 Ω/km
Mutual capacitance		52 pF/m
Characteristic impedance		75 Ω ± 2 Ω
Velocity ratio		82 %
Screening factor	30 MHz – 1000 MHz	> 110 dB
	1000 MHz – 2000 MHz	> 100 dB
	2000 MHz – 3000 MHz	> 100 dB
Transfer impedance	5 MHz – 30 MHz	≤ 5 mΩ/m
Electrical strength	Dielectric	2 kV _{DC} 1 min
	Sheath	3.75 kV _{DC} 1 min

Electrical data

at 20°C

Attenuation (dB/100m)		Return loss (dB)	
Frequency (MHz)		Frequency (MHz)	
	nominal		
5	1.6	5 – 30	> 26
50	4.3	30 – 470	> 24
100	6.2	470 – 1000	> 20
200	8.7	1000 – 3000	> 18
400	12.5		
862	18.6		
950	19.8		
1350	23.7		
1750	27.2		
2150	30.5		
3000	36.9		

Technical data

Product code	Cable type	Weight kg/km	Standard delivery length m	Drum size *PWD	Copper content	Tensile force N	Bending radius mm	Storage
1002581	Coax10 AD 10 S FRNC-C black without printing	52	1000	500/200/3 60	21.9	175	35	inside
1002582	Coax10 AD 10 S FRNC-C white without printing	52	1000	500/200/3 60	21.9	175	35	inside
1002583	Coax10 AD 10 S FRNC-C blue	52	1000	500/200/3 60	21.9	175	35	inside
1025344	Coax10 AD 10 S FRNC-C white	52	1000	500/200/3 60	21.9	175	35	inside

*PWD (plywood drum)

Coax10 AD 10 S

Product Code Table

Product Description	Product Code	PG Reference Code	PG Part Number
Coax10 AD 10 S FRNC-C BK no print		--	60013833
Coax10 AD 10 S FRNC-C BK no print 500DW	1002581-00500DW	--	60013834
Coax10 AD 10 S FRNC-C BK no print 1000DW	1002581-01000DW	--	60013835
Coax10 AD 10 S FRNC-C WH no print		60013836	60013836
Coax10 AD 10 S FRNC-C WH no print 500DW	1002582-00500DW	60013836	60013837
Coax10 AD 10 S FRNC-C WH no print 1000DW	1002582-01000DW	60013836	60013838
Coax10 AD 10 S FRNC-C BU		60013839	60013839
Coax10 AD 10 S FRNC-C BU 500DW	1002583-00500DW	60013839	60013840
Coax10 AD 10 S FRNC-C BU 1000DW	1002583-01000DW	60013839	60013841
Coax10 AD 10 S FRNC-C WH		60013843	60013843

© PRYSMIAN GROUP 2012, All Rights Reserved

All sizes and values without tolerances are reference values. Specifications are for product as supplied by Prysmian Group: any modification or alteration afterwards of product may give different result.

The information contained within this document must not be copied, reprinted or reproduced in any form, either wholly or in part, without the written consent of Prysmian Group. The information is believed to be correct at the time of issue. Prysmian Group reserves the right to amend this specification without prior notice. This specification is not contractually valid unless specifically authorised by Prysmian Group.